



Overview

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software Documentation CD 2 x detachable IEC C13 to IEC C14 power cords USB cable
Performance multiplier	1
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Workstation
UPS size	WS
Value multiplier	1

Physical

Farge	Beige
Dybde	28,4 cm
Høyde	16,5 cm
Montasjeplassering	Front
Mounting preference	No preference
Vekt	6,03 kg
Monteringsmetode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Bredde	9,1 cm

Input

Network frequency	47...63 Hz 50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 60320 C14
Input voltage limits	160...286 V adjustable 180...266 V
Maximum input current	7 A
Brytekapasitet, A	7 A

Antall kabler	2
Forsyningsspenning	230 V

Output

Merkeeffekt i W	400 W
Maximum configurable power in W	400 W
Output frequency	47...63 Hz sync to mains 50/60 Hz +/- 1 Hz unsynchronised
UPS type	Standby
Wave type	Stepped approximation to a sinewave
Nb of power socket outlets	3 IEC 60320 C13 1 IEC 60320 C13 surge 2 IEC Jumpers surge
Curve equation	Efficiency
Curve fixed loss	0,0102
Curve load maximum	100 %
Curve load minimum	2 %
Curve proportional loss	0
Curve square loss	0,0014
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF =
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	650 VA
Merkeeffekt VA	650 VA
Transfer time	6 ms typical : 10 ms maximum

Conformance

Produktsertifikater	A-Tick C-Tick CE GOST NEMKO
Equipment protection policy	Lifetime : 100000 euros Lifetime : 50000 GBP

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	5...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15...45 °C
Storage Relative Humidity	5...95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	45 dBA
Show note OP temperature	No

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 t
Number of battery replacement quantity	1
Liquid value	0
Batterispenningen	12 V
Kapasitet på batteri	9,0 Ah
Battery curve	C
Battery charger power	12 W rated
Battery power in VAH	95 VAh capacity 95 VAh runtime
Batterilevetid	4...6 år
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0

Communications & Management

Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	310 J
Data line protection	RJ45 analog phone line for phone/fax/modem/DSL

Packing Units

Forpakning 1 vekt	7,31 kg
Forpakning 1 høyde	49,4 cm
Forpakning 1 bredde	18,5 cm
Forpakning 1 lengde	41,5 cm
SCC14	10731304219788
Antall enheter forpakning 2	1
Forpakning 2 vekt	7,30 kg
Antall enheter forpakning 3	48

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------