



Overview

Presentasjon	Accessory solutions to tailor the Smart-UPS to meet your specific needs.
Leveringstid	Usually in Stock

General

Tilgjengelig utstyr	Installation guide Mounting hardware Brukermanual
---------------------	---

Physical

Farge	Sort
Dybde	66 cm
Høyde	13 cm
Vekt	56,82 kg
Bredde	43,2 cm

Input

Input current limits	30 A
Load capacity	5000 VA
Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Forsyningsspenning	230 V

Output

Output connector type	Hard wire 3-wire (H N + E) 1
Output voltage	230 V

Conformance

Produktsertifikater	C-Tick CE
Standarder	EN 50091-1 EN 55022 Class B EN 55024 EN 60950 EN 61000-3-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-25...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0,00...15240,00 m

Packing Units

Forpakning 1 vekt	63,64 kg
Forpakning 1 høyde	34,7 cm
Forpakning 1 bredde	60,3 cm
Forpakning 1 lengde	98 cm
SCC14	10731304217791
Antall enheter forpakning 3	6

Offer Sustainability

Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	 REACH-erklæring
EU RoHS-direktiv	I samsvar  EU RoHS-erklæring
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	 Ja
Miljøinformasjon	 Produktmiljøprofil
Produktets livssyklus	 Informasjon Om Levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available

Contractual warranty

Garanti	2 years repair or replace
---------	---------------------------