

# SMX750I

## APC Smart-UPS X 750VA Rack/Tower LCD 230V



### Overview

|              |                                                                                                                                                                                   |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentasjon | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
| Leveringstid | Usually Ships within 2 Weeks                                                                                                                                                      |

### General

|                                     |                                                                                                                                                                    |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inkludert utstyr                    | CD with software<br>Documentation CD<br>Installation guide<br>Rack mounting brackets<br>Removable support feet<br>Smart UPS signalling RS-232 cable<br>User manual |
| Product web sub-family              | Extended run                                                                                                                                                       |
| Number of tare power                | 7 W                                                                                                                                                                |
| Number of power module free slots   | 0                                                                                                                                                                  |
| Number of power module filled slots | 0                                                                                                                                                                  |
| Redundant                           | No                                                                                                                                                                 |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Kabellengde         | 1,83 m                |
| Number of rack unit | 2U                    |
| Farge               | Black                 |
| Dybde               | 49 cm                 |
| Høyde               | 8,9 cm                |
| Mounting preference | Lower                 |
| Vekt                | 22,05 kg              |
| Monteringsmetode    | Rack-mounted with kit |
| Two post mountable  | 1                     |
| USB compatible      | No                    |
| Bredde              | 43,2 cm               |

### Input

|                      |                                      |
|----------------------|--------------------------------------|
| Network frequency    | 50/60 Hz +/- 3 Hz auto-sensing       |
| Plug standard        | IEC 320 C14                          |
| Input voltage limits | 151...302 V Justerbar<br>160...286 V |
| Inputvolt_other      | 220 V<br>240 V                       |
| Antall kabler        | 1                                    |
| Forsyningsspenning   | 230 V                                |

## Output

|                                  |                                 |
|----------------------------------|---------------------------------|
| Merkeeffekt i W                  | 600 W                           |
| Maximum configurable power in W  | 600 W                           |
| Harmonic distortion              | Mindre enn 5 %                  |
| Output frequency                 | 50/60 Hz +/- 3 Hz sync to mains |
| UPS type                         | Line interactive                |
| Wave type                        | Sine wave                       |
| Nb of power socket outlets       | 8 IEC 320 C13<br>2 IEC Jumpers  |
| Output voltage                   | 230 V                           |
| Maximum configurable power in VA | 750 VA                          |
| Merkeeffekt VA                   | 750 VA                          |

## Conformance

|                     |                                  |
|---------------------|----------------------------------|
| Produktsertifikater | CE<br>RCM<br>VDE<br>EAC          |
| Standarder          | EN/IEC 62040-1<br>EN/IEC 62040-2 |

## Environmental

|                                  |                   |
|----------------------------------|-------------------|
| Omgivelsestemperatur drift       | 0...40 °C         |
| Relativ fuktighet                | 0...95 %          |
| Driftshøyde                      | 0...10000 ft      |
| Omgivelsestemperatur for lagring | -15...45 °C       |
| Storage Relative Humidity        | 0...95 %          |
| Storage altitude                 | 0,00...15240,00 m |
| Akkustikknivå                    | 40 dBA            |
| Varmeavgivelse                   | 69 Btu/t          |

## Batteries & Runtime

|                                        |                                                                                                                               |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Batteritype                            | Bly-syre batteri                                                                                                              |
| Number of battery filled slots         | 1                                                                                                                             |
| Number of battery free slots           | 1                                                                                                                             |
| Battery recharge time                  | 3 t                                                                                                                           |
| Number of battery replacement quantity | 1                                                                                                                             |
| Liquid value                           | 0                                                                                                                             |
| Beskyttelse mot overstrøm              | 60 A                                                                                                                          |
| Battery charger power                  | 104 W rated                                                                                                                   |
| Battery power in VAh                   | 312 VAh runtime                                                                                                               |
| Batterilevetid                         | 3...5 år                                                                                                                      |
| Battery option                         | SMX48RMBP2U 1 938 VAh<br>SMX48RMBP2U 2 1563 VAh<br>SMX48RMBP2U 3 2188 VAh<br>SMX48RMBP2U 4 2613 VAh<br>SMX48RMBP2U 5 3438 VAh |
| Extended runtime                       | 0                                                                                                                             |

## Communications & Management

|                |                                                                                        |
|----------------|----------------------------------------------------------------------------------------|
| Ledige plasser | 1                                                                                      |
| Control panel  | Multifunction LCD status and control console                                           |
| Alarm          | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

## Surge Protection and Filtering

|                   |                                                                                                                |
|-------------------|----------------------------------------------------------------------------------------------------------------|
| Surge energy rate | 645 J                                                                                                          |
| Noise suppression | Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449 |

## Packing Units

|                             |         |
|-----------------------------|---------|
| Forpakning 1 vekt           | 26,5 kg |
| Forpakning 1 høyde          | 24,6 cm |
| Forpakning 1 bredde         | 58,9 cm |
| Forpakning 1 lengde         | 62 cm   |
| Antall enheter forpakning 3 | 8       |

## Offer Sustainability

|                                 |                                                                                                                                |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Produktets miljøstatus          | Green Premium miljømerket produkt                                                                                              |
| REACH-regelverk                 |  <a href="#">REACH-erklæring</a>              |
| EU RoHS-direktiv                | I samsvar  <a href="#">EU RoHS-erklæring</a>  |
| Kvikksølvfri                    | Ja                                                                                                                             |
| Informasjon om RoHS-unntak      |  <a href="#">Ja</a>                           |
| Miljøinformasjon                |  <a href="#">Produktmiljøprofil</a>           |
| Produktets livssyklus           |  <a href="#">Informasjon Om Levetidsslutt</a> |
| WEEE                            | Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.     |
| Optimalisert energieffektivitet | Energieffektivt produkt                                                                                                        |
| Take-back                       | Take-back program available                                                                                                    |

## Contractual warranty

|         |                                                                       |
|---------|-----------------------------------------------------------------------|
| Garanti | 3 years repair or replace (excluding battery) and 2 years for battery |
|---------|-----------------------------------------------------------------------|