

Mer om VW3A46112

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**VW3A46112****Passiva filter 150A 400V 50Hz 10%THDi**

El-nummer: 4177436

EAN: 3606480640032

Last ned produktdatablad for VW3A46112

Karakteristikk**Teknisk informasjon**

Produkt eller type komponent	Passive filter
Produktspesifikk applikasjon	Reduction of current harmonics

Komplementær

Serie kompatibilitet	Altivar 61 Altivar Process ATV600 Altivar Process ATV900 Altivar 71
[Us] matespenning	400 V +/- 10 %
Power supply frequency	50 Hz +/- 2 %
Kv antum per stasjon	1 filter per drive for variable speed drive ATV61H motor: 90 kW/125 hp 1 filter per drive for variable speed drive ATV61W motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV61W motor: 90 kW/125 hp 1 filter per drive for variable speed drive ATV71H motor: 90 kW/125 hp 1 filter per drive for variable speed drive ATV61H motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV71H motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV71W motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV71Q motor: 90 kW/125 hp 1 filter per drive for variable speed drive ATV650 veggmontering, motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV630 veggmontering, motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV950 veggmontering, motor: 75 kW/100 hp 1 filter per drive for variable speed drive ATV930 veggmontering, motor: 75 kW/100 hp
[In] merkestrøm	144 A for inngang 150 A for utgang
Antall faser i nettverket	3 faser
THDI	10 % for variable speed drive ATV61H motor: 90 kW/125 hp 10 % for variable speed drive ATV61W motor: 75 kW/100 hp 10 % for variable speed drive ATV61W motor: 90 kW/125 hp 10 % for variable speed drive ATV71H motor: 90 kW/125 hp 16 % for variable speed drive ATV61H motor: 75 kW/100 hp 16 % for variable speed drive ATV71H motor: 75 kW/100 hp 16 % for variable speed drive ATV71W motor: 75 kW/100 hp 10 % for variable speed drive ATV71Q motor: 90 kW/125 hp 10 % for variable speed drive ATV650 motor: 75 kW/100 hp 10 % for variable speed drive ATV630 motor: 75 kW/100 hp 10 % for variable speed drive ATV950 motor: 75 kW/100 hp 10 % for variable speed drive ATV930 motor: 75 kW/100 hp
Max strøm	1.5 x nominell strøm (varighet = 60 s)
Effektivitet	98 %
Varmetap	692 W

Cos phi	1 (150% av linjestrøm) 0,85 (75% av linjestrøm) 0,99 (100% av linjestrøm)
Elektrisk tilkobling	A, B klemme, tilkoblingskapasitet: 2.5 mm2 X1-1...X2-3 klemme, tilkoblingskapasitet: 2.5 ... 90 mm²
Elektrisk isolasjonsklasse	Klasse F
Vekt	85 kg
Miljø	
IP-grad	IP20 IP55 (kabinettmontering)
Vibrasjonsmotstand	2mm topp til topp (f= 5...13,2 Hz) i samsvar med EN 60068-2-6 0.7 gn (f= 13,2...150 Hz) i samsvar med EN 60068-2-6
Relativ fuktighet	5...85 % uten kondens
Omgivelsestemperatur for drift	45...60 °C (med strømlastreduksjon på 3 % per °C) 5...45 °C (uten strøm belastningsreduksjon)
Omgivende lufttemperatur for oppbevaring	-25...55 °C lagring i originalemballasje -25...65 °C under transport
Operating altitude	<= 1000 m uten strøm belastningsreduksjon > 1000...4000 m med dagens effektreduksjon 5% per 1000 m
Standarder	EN/IEC 61000-2-2 G5/4 engineering recommendation EN/IEC 61000-3-12 EN/IEC 61000-3-2 EN/IEC 61000-2-4 EN/IEC 61000-3-4
Bærekraftig	
EU RoHS-direktiv	Proaktivt i samsvar (Produktet inngår ikke i EUs RoHS direktivet) EU RoHS-erklæring
Fri for giftige tungmetaller	Ja
Kvikksølvfri	Ja
Informasjon om RoHS-unntak	Ja
Kinas RoHS-forskrift	Kinas RoHS-erklæring
Garantiperiode	
Garanti	18 måneder