



Oversikt

Leveringstid	Usually in Stock
--------------	------------------

General

Inkludert utstyr	CD with software Brukermanual USB kabel
------------------	---

Physical

Dybde	63,2 cm
Høyde	8,6 cm
Vekt	27 kg
Bredde	43,7 cm

Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	160...280 V
Inputvolt_other	220 V 240 V
Verntype på inngang	Circuit breaker and fuse
Forsyningsspenning	230 V

Output

Merkeeffekt i W	2400 W
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest faktor	3:1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	6 IEC 60320 C13 1 IEC 60320 C19
Bypass type	Internal bypass (automatic and manual)
Output voltage	230 V

Conformance

Produktsertifikater	CE
Standarder	IEC 62040-1-1 IEC 62040-1-2

Environmental

Omgivelsestemperatur drift	0...40 °C
Relativ fuktighet	0...95 % ikke-kondenserende
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-20...50 °C
Storage altitude	0,00...14999,82 m

Batteries & Runtime

Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 t
Liquid value	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Forpakkingsinformasjon

Forpakning 1 vekt	31,7 kg
Forpakning 1 høyde	22,9 cm
Forpakning 1 bredde	56,9 cm
Forpakning 1 lengde	79,5 cm

Garantiperiode

Garanti	2 years repair or replace
---------	---------------------------