

## Mer om SMT1000I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-  
Electric tools

**SMT1000I**  
**APC Smart-UPS 1000VA LCD 230V**

EI-nummer: 6605325

EAN: 0731304268673



by Schneider Electric



Last ned produktdatablad for SMT1000I

## Karakteristikk

## Oversikt

|              |                                                                                                                                                                                   |
|--------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Presentasjon | Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices. |
| Leveringstid | Usually Ships within 2 Weeks                                                                                                                                                      |

## General

|                                     |                                                                                                              |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------|
| Inkludert utstyr                    | CD with software<br>Documentation CD<br>Installation guide<br>Smart UPS signalling RS-232 cable<br>USB cable |
| Performance multiplier              | 1                                                                                                            |
| Number of tare power                | 30 W                                                                                                         |
| Number of power module free slots   | 0                                                                                                            |
| Number of power module filled slots | 0                                                                                                            |
| Redundant                           | No                                                                                                           |
| Size UPS version                    | Internetworking<br>Server<br>Telecom                                                                         |
| UPS size                            | S                                                                                                            |
| Value multiplier                    | 1                                                                                                            |

## Physical

|                     |                    |
|---------------------|--------------------|
| Farge               | Black              |
| Dybde               | 43,9 cm            |
| Høyde               | 21,9 cm            |
| Montasjeplassering  | Front              |
| Mounting preference | No preference      |
| Vekt                | 18,86 kg           |
| Monteringsmetode    | Not rack-mountable |
| Two post mountable  | 0                  |
| USB compatible      | No                 |
| Bredde              | 17,1 cm            |

|                                  |                                                                                                                                                                                                                                                                |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Input</b>                     |                                                                                                                                                                                                                                                                |
| Network frequency                | 50/60 Hz +/- 3 Hz auto-sensing                                                                                                                                                                                                                                 |
| Plug standard                    | IEC 320 C14                                                                                                                                                                                                                                                    |
| Input voltage limits             | 151...302 V adjustable<br>160...286 V                                                                                                                                                                                                                          |
| Inputvolt_other                  | 220 V<br>240 V                                                                                                                                                                                                                                                 |
| Forsyningsspenning               | 230 V                                                                                                                                                                                                                                                          |
| <b>Output</b>                    |                                                                                                                                                                                                                                                                |
| Merkeeffekt i W                  | 700 W                                                                                                                                                                                                                                                          |
| Maximum configurable power in W  | 700 W                                                                                                                                                                                                                                                          |
| Harmonic distortion              | Mindre enn 5 % ved full last                                                                                                                                                                                                                                   |
| Output frequency                 | 47...53 Hz for 50 Hz nominal sync to mains<br>57...63 Hz for 60 Hz nominal sync to mains                                                                                                                                                                       |
| Output voltage                   | 220 V<br>240 V                                                                                                                                                                                                                                                 |
| UPS type                         | Line interactive                                                                                                                                                                                                                                               |
| Wave type                        | Sine wave                                                                                                                                                                                                                                                      |
| Nb of power socket outlets       | 8 IEC 320 C13<br>2 IEC Jumpers                                                                                                                                                                                                                                 |
| Curve equation                   | Efficiency                                                                                                                                                                                                                                                     |
| Curve fixed loss                 | 0,0127                                                                                                                                                                                                                                                         |
| Curve load maximum               | 100 %                                                                                                                                                                                                                                                          |
| Curve load minimum               | 2 %                                                                                                                                                                                                                                                            |
| Curve proportional loss          | 0                                                                                                                                                                                                                                                              |
| Curve square loss                | 0,0015                                                                                                                                                                                                                                                         |
| Curve X-axis maximum             | 100 %                                                                                                                                                                                                                                                          |
| Curve test cond ID               | Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = |
| Curve X-axis minimum             | 0 %                                                                                                                                                                                                                                                            |
| Curve X-axis title               | Load                                                                                                                                                                                                                                                           |
| Curve X-axis units               | Percentage                                                                                                                                                                                                                                                     |
| Curve Y-axis maximum             | 100 %                                                                                                                                                                                                                                                          |
| Curve Y-axis minimum             | 50 %                                                                                                                                                                                                                                                           |
| Curve Y-axis title               | Efficiency                                                                                                                                                                                                                                                     |
| Curve Y-axis units               | Percentage                                                                                                                                                                                                                                                     |
| Graph display                    | 1                                                                                                                                                                                                                                                              |
| Output voltage                   | 230 V                                                                                                                                                                                                                                                          |
| Maximum configurable power in VA | 1000 VA                                                                                                                                                                                                                                                        |
| Merkeeffekt VA                   | 1000 VA                                                                                                                                                                                                                                                        |
| <b>Conformance</b>               |                                                                                                                                                                                                                                                                |

|                                        |                                                                                                                  |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------|
| Produktsertifikater                    | CE<br>EAC<br>RCM<br>VDE                                                                                          |
| Standarder                             | EN/IEC 62040-1<br>EN/IEC 62040-2                                                                                 |
| <b>Environmental</b>                   |                                                                                                                  |
| Omgivelsestemperatur drift             | 0..40 °C                                                                                                         |
| Relativ fuktighet                      | 0..95 %                                                                                                          |
| Driftshøyde                            | 0...10000 ft                                                                                                     |
| Omgivelsestemperatur for lagring       | -15..45 °C                                                                                                       |
| Storage Relative Humidity              | 0..95 %                                                                                                          |
| Storage altitude                       | 0,00...15240,00 m                                                                                                |
| Akkustikknivå                          | 41 dBA                                                                                                           |
| Varmeavgivelse                         | 100 Btu/t                                                                                                        |
| Show note OP temperature               | No                                                                                                               |
| <b>Batteries &amp; Runtime</b>         |                                                                                                                  |
| Batteritype                            | Bly-syre batteri                                                                                                 |
| Number of battery filled slots         | 0                                                                                                                |
| Number of battery free slots           | 0                                                                                                                |
| Battery recharge time                  | 3 t                                                                                                              |
| Number of battery replacement quantity | 1                                                                                                                |
| Tilleggsinformasjon                    | Configurable for 220 : 230 or 240 nominal output voltage                                                         |
| Liquid value                           | 0                                                                                                                |
| Battery curve                          | Z                                                                                                                |
| Battery charger power                  | 88 W rated                                                                                                       |
| Battery power in VAH                   | 264 VAh runtime                                                                                                  |
| Batterilevetid                         | 3..5 år                                                                                                          |
| Extended runtime                       | 0                                                                                                                |
| <b>Communications &amp; Management</b> |                                                                                                                  |
| Ledige plasser                         | 1                                                                                                                |
| Control panel                          | Multifunction LCD status and control console                                                                     |
| Alarm                                  | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm                           |
| Emergency power off                    | Optional                                                                                                         |
| <b>Surge Protection and Filtering</b>  |                                                                                                                  |
| Surge energy rate                      | 459 J                                                                                                            |
| Noise suppression                      | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449 |
| <b>Packing Units</b>                   |                                                                                                                  |
| Forpakning 1 vekt                      | 22,77 kg                                                                                                         |
| Forpakning 1 høyde                     | 37,6 cm                                                                                                          |

|                                 |                                                                                                                            |
|---------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Forpakning 1 bredde             | 32,8 cm                                                                                                                    |
| Forpakning 1 lengde             | 59,5 cm                                                                                                                    |
| SCC14                           | 731304268673                                                                                                               |
| Antall enheter forpakning 3     | 12                                                                                                                         |
| <b>Offer Sustainability</b>     |                                                                                                                            |
| Produktets miljøstatus          | Green Premium miljømerket produkt                                                                                          |
| REACH-regelverk                 | <a href="#">REACH-erklæring</a>                                                                                            |
| EU RoHS-direktiv                | I samsvar<br><a href="#">EU RoHS-erklæring</a>                                                                             |
| Kvikksølv fri                   | Ja                                                                                                                         |
| Informasjon om RoHS-unntak      | <a href="#">Ja</a>                                                                                                         |
| Miljøinformasjon                | <a href="#">Produktmiljøprofil</a>                                                                                         |
| Produktets livssyklus           | <a href="#">Informasjon om levetidsslutt</a>                                                                               |
| WEEE                            | Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall. |
| Optimalisert energieffektivitet | Energieffektivt produkt                                                                                                    |
| Take-back                       | Take-back program available                                                                                                |
| <b>Garantiperiode</b>           |                                                                                                                            |
| Garanti                         | 3 years repair or replace (excluding battery) and 2 years for battery                                                      |