

Mer om SMX750I

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools

**SMX750I****APC Smart-UPS X 750VA Rack/Tower LCD 230V**

EI-nummer: 6605329

EAN: 0731304268581



by Schneider Electric



Last ned produktdatablad for SMX750I



Karakteristikk

Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

General

Inkludert utstyr	CD with software Documentation CD Installation guide Rack mounting brackets Removable support feet Smart UPS signalling RS-232 cable User manual
Product web sub-family	Extended run
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	1,83 m
Number of rack unit	2U
Farge	Black
Dybde	49 cm
Høyde	8,9 cm
Mounting preference	Lower
Vekt	22,05 kg
Monteringsmetode	Rack-mounted with kit
Two post mountable	1
USB compatible	No
Bredde	43,2 cm

Input

Network frequency	50/60 Hz +/- 3 Hz automatisk gjenkjenning
-------------------	---

Plug standard	IEC 320 C14
Input voltage limits	151...302 V Justbar 160...286 V
Inputvolt_other	220 V 240 V
Antall kabler	1
Forsyningsspenning	230 V
Output	
Merkeeffekt i W	600 W
Maximum configurable power in W	600 W
Harmonic distortion	Mindre enn 5 %
Output frequency	50/60 Hz +/- 3 Hz sync to mains
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers
Output voltage	230 V
Maximum configurable power in VA	750 VA
Merkeeffekt VA	750 VA
Conformance	
Produktsertifikater	CE RCM VDE EAC
Standarder	EN/IEC 62040-1 EN/IEC 62040-2
Environmental	
Omgivelsestemperatur drift	0..40 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage Relative Humidity	0..95 %
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	69 Btu/t
Batteries & Runtime	
Batteritype	Bly-syre batteri
Number of battery filled slots	1
Number of battery free slots	1
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Beskyttelse mot overstrøm	60 A
Battery charger power	104 W rated

Battery power in VAh	312 VAh runtime
Batterilevetid	3..5 år
Battery option	SMX48RMBP2U 1 938 VAh SMX48RMBP2U 2 1563 VAh SMX48RMBP2U 3 2188 VAh SMX48RMBP2U 4 2613 VAh SMX48RMBP2U 5 3438 VAh
Extended runtime	0
Communications & Management	
Ledige plasser	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Surge Protection and Filtering	
Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Packing Units	
Forpakning 1 vekt	26,5 kg
Forpakning 1 høyde	24,6 cm
Forpakning 1 bredde	58,9 cm
Forpakning 1 lengde	62 cm
Antall enheter forpakning 3	8
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Contractual warranty	
Garanti	3 years repair or replace (excluding battery) and 2 years for battery