

Mer om SMX1500RMI2UNC

- [Karakteristikk](#)
- [Download & Dokumenter](#)

Discover your Schneider-
Electric tools



SMX1500RMI2UNC

APC Smart-UPS X 1500VA Rack/Tower LCD 230V with Network Card

EI-nummer: 6605332

EAN: 0731304281702



Last ned produktdatablad for SMX1500RMI2UNC

Karakteristikk

Overview

Presentasjon	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Leveringstid	Usually Ships within 2 Weeks

General

Product web sub-family	Network card pre-installed
Number of tare power	7 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Kabellengde	1,83 m
Number of rack unit	2U
Farge	Black
Dybde	49 cm
Høyde	8,9 cm
Mounting preference	Lower
Vekt	24,82 kg
Monteringsmetode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Bredde	43,2 cm

Input

Brytekapasitet, A	10 A
Antall kabler	1

Output

Merkeeffekt i W	1200 W
-----------------	--------

Maximum configurable power in W	1200 W
Harmonic distortion	Mindre enn 5 %
UPS type	Line interactive
Wave type	Sine wave
Maximum configurable power in VA	1500 VA
Merkeeffekt VA	1500 VA
Conformance	
Produktsertifikater	C-Tick CE VDE EAC
Standarder	EN 50091-1 EN 50091-2
Environmental	
Omgivelsestemperatur drift	0..45 °C
Relativ fuktighet	0..95 %
Driftshøyde	0...10000 ft
Omgivelsestemperatur for lagring	-15..45 °C
Storage altitude	0,00...15240,00 m
Akkustikknivå	40 dBA
Varmeavgivelse	133 Btu/t
Batteries & Runtime	
Batteritype	Bly-syre batteri
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 t
Number of battery replacement quantity	1
Liquid value	0
Batterilevetid	3..5 år
Extended runtime	0
Communications & Management	
Ledige plasser	0
Preinstalled device	Network management card 2 with environmental monitoring
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes
Surge Protection and Filtering	
Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449
Packing Units	

Forpakning 1 vekt	30 kg
Forpakning 1 høyde	24,6 cm
Forpakning 1 bredde	58,9 cm
Forpakning 1 lengde	62 cm
Antall enheter forpakning 3	8
Offer Sustainability	
Produktets miljøstatus	Green Premium miljømerket produkt
REACH-regelverk	REACH-erklæring
EU RoHS-direktiv	I samsvar EU RoHS-erklæring
Kvikksølv fri	Ja
Informasjon om RoHS-unntak	Ja
Miljøinformasjon	Produktmiljøprofil
Produktets livssyklus	Informasjon om levetidsslutt
WEEE	Innen EU må produktet avhendes i henhold til bestemte regler for avfallshåndtering og aldri kastes som husholdningsavfall.
Optimalisert energieffektivitet	Energieffektivt produkt
Take-back	Take-back program available
Contractual warranty	
Garanti	3 years repair or replace (excluding battery) and 2 years for battery