

HIGHLITE IP65

To our growing range of industrial luminaires, we now welcome Highlite IP65 – a highly efficient highbay luminaire with the emphasis on maximum light and minimum maintenance. Highlite IP65 is an industrial luminaire adapted for the factory environment, as well as for the crossfit studio or the supermarket, can handle a height of up to 25 meters. The luminaire is D-marked, IK08-classified and is best in projects where a lot of light is required. Mounted as a pendant or in a fixed ceiling with a ceiling bracket as an accessory. More accessories including reflectors in aluminium, black and line prism to change the appearance and increase anti-glare, as well as strong chains for suspension. The luminaire has a replaceable driver, three metre connection cable and simple installation with the snap hook provided. A real highlight!



**HIGHBAY LUMINAIRE
– MORE LIGHT FOR
THE MONEY**

- Highly efficient LED luminaire, up to 31500lm for heights up to 25m
- D-marked according to SS-EN 60598-2-24 - for spaces with a high fire risk
- Easy to install– replaceable driver, 3m connection cable and mounting with hook
- For tough environments – IP65 and IK08
- Reflectors, suspension kit and ceiling and wall fixing brackets as accessories







Highlite IP65 with reflectors



HIGHLITE IP65





GTIN	Type	Color	Colour Temperature	Luminaire Lumen	Beam Angle	Luminaire efficiency	Power Luminaire
7392971145914	S	Black	4000K	16100lm	60°	164lm/W	100W
7392971145921	S	Black	4000K	15800lm	90°	158lm/W	100W
7392971145938	S	Black	4000K	16400lm	120°	161lm/W	100W
7392971145945 ¹	S DALI	Black	4000K	15000lm	60°	150lm/W	100W
7392971145952 ¹	S DALI	Black	4000K	15100lm	90°	151lm/W	100W
7392971145969 ¹	S DALI	Black	4000K	15100lm	120°	151lm/W	100W
7392971145976	L	Black	4000K	30200lm	60°	151lm/W	200W
7392971145983	L	Black	4000K	29900lm	90°	150lm/W	200W
7392971145990	L	Black	4000K	31500lm	120°	158lm/W	200W
7392971146003 ¹	L DALI	Black	4000K	29000lm	60°	145lm/W	200W
7392971146010 ¹	L DALI	Black	4000K	29500lm	90°	148lm/W	200W
7392971146027 ¹	L DALI	Black	4000K	29800lm	120°	149lm/W	200W



REFLECTOR HIGHLITE




GTIN	Type	Color
7392971146034	Prism	Transparent
7392971146041	Alu	Aluminium
7392971146058	Alu	Svart



CEILING/WALL BRACKET ADJUSTABLE HIGHLITE



GTIN	Type	Adjustable
7392971146065	Black	90°



SUSPENSION KIT HIGHLITE



GTIN	Type	Length
7392971146072	Black	2m

