



FDV Dokumentasjon

KC6 		Minikontaktorer KC6			
		Varetekst	El.Nr.	ABB Art.Nr.	EAN/GTIN
		KC6-22Z 110V DC	4190537	GJH1213001R0224	4013614049675
Forvaltning		Normer			
		IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1			
Drift		Renhold	Ikke krav til renhold		
		Energiforbruk	Average Holding Value 50Hz 3.5 volt-ampere Average Pull-in Value 50Hz 3.5 volt-ampere		
		Henvisninger	Katalog ID : 1SBC100192C02		
Vedlikehold		Rutiner	Ingen krav til periodisk vedlikehold		
		Levetid			
		Annet			
Generelt		Dimensjoner: HxBxD = 57,5x52,5x46,5 millimetre Ie: AC15=4/4/3A (24/240/400V), DC13=1,5/0,04A (24/250V) Ue= 12-240V DC, 12-500V AC Main dimensions mm, inches			
		  KC6			
Produsent	Navn	Adresse	Tlf	E-Post	
	ABB AS Low Voltage Products	Postboks 94 1375 Billingstad	24 16 54 00	automasjonsprodukter@no.abb.com	