

FDV

5

ELnumber	Material No.	Material Discription
4363620	1SCA105088R1001	Fjerde pol OTPL125FD
4363621	1SCA105090R1001	Fjerde pol OTPL125FP
4363615	1SCA105716R1001	Fjerde pol OTPL40FD
4363614	1SCA105717R1001	Fjerde pol OTPL40FP
4363617	1SCA105451R1001	Fjerde pol OTPL80FD
4363616	1SCA105452R1001	Fjerde pol OTPL80FP
4363618	1SCA105096R1001	Fjerde pol OTPS125FD
4363619	1SCA105099R1001	Fjerde pol OTPS125FP
4363611	1SCA104999R1001	Fjerde pol OTPS40FDN1
4363612	1SCA104998R1001	Fjerde pol OTPS40FDN2
4363606	1SCA105001R1001	Fjerde pol OTPS40FPN1
4363607	1SCA105000R1001	Fjerde pol OTPS40FPN2
4363605	1SCA105458R1001	Fjerde pol OTPS80FD
4363613	1SCA105461R1001	Fjerde pol OTPS80FP




ABB AS, Low Voltage Products

Inngår i Part of
ABB AS

Adresse Address
Postboks 100 Sentrum
Amm. Aallsgt. 97
3701 SKIEN
Norway

Telefon Phone
Nasjonal 03500
International +47 22872000

Web:
www.abb.no/automasjonsprodukter
Product catalogue online:
www.abblvp.no

Foretaksregisteret
Register of Business Enterprises
NO982 085 160MVA



Handled by
Matti Tuononen

Date
27/06/2014

Pages
1 (2)

Letter of confirmation

To whom it may concern

We hereby confirm that the listed ABB products can be used in ambients specified below:

OT16F...160E_ , OT16...125F_C_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.
 - o At - 40C the maximum number of cold starts is 100 operations.
 - o In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

OT200...4000E_ , OT160...3200E_C_ , OS32G_ ... OS1250_ , OTDC16_ ... 500_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.

ABB Oy

Low Voltage Products
Business Identity Code: 0763403-0 VAT-Muotitie 2 A
code FI07634030
Domicile: Helsinki

Visiting Address
Muotitie 2 A
FI-65320 Vaasa
FINLAND

Postal Address
P.O. Box 622
FI-65101 Vaasa
FINLAND


Company Address
Strömbergintie 1
FI-00380 Helsinki
FINLAND

Telephone
+358 10 22 11
Telefax
+358 10 22 45708

Internet
www.abb.fi
e-mail:
first name.last name
@fi.abb.com

- At - 35C the endurance values according to the requirements of category B.
- In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

Yours faithfully



Martti Tuononen

Product manager