



FDV

6

ELnumber	Material No.	Material Discription
4363577	1SCA102680R1001	HANDLE OHBS1AH
4337838	1SCA022380R9740	HÅNDTAK GRÅ OHG 65J6
4337807	1SCA022380R9820	HÅNDTAK GUL/RØD OHY65J6
4337677	1SCA022439R4050	HÅNDTAK OHB4
4363576	1SCA108252R1001	Håndtak OHBS12
4363579	1SCA105210R1001	Håndtak OHBS1AH1
4363590	1SCA105211R1001	Håndtak OHBS1PH
4363591	1SCA105212R1001	Håndtak OHBS1RH
4363583	1SCA105213R1001	Håndtak OHBS2AJ
4363593	1SCA105215R1001	Håndtak OHBS2AJ1
4363585	1SCA105220R1001	Håndtak OHBS2AJE011
4363622	1SCA105221R1001	Håndtak OHBS2AJM
4363586	1SCA105231R1001	Håndtak OHBS2PJ
4363588	1SCA105232R1001	Håndtak OHBS2RJ
4363581	1SCA105234R1001	Håndtak OHBS3AH
4363578	1SCA105290R1001	Håndtak OHYS1AH
4363580	1SCA105291R1001	Håndtak OHYS1AH1
4363592	1SCA105294R1001	Håndtak OHYS1PH
4363584	1SCA105296R1001	Håndtak OHYS2AJ
4363623	1SCA105303R1001	Håndtak OHYS2AJM
4363587	1SCA105322R1001	Håndtak OHYS2PJ
4363589	1SCA105323R1001	Håndtak OHYS2RJ
4363582	1SCA105325R1001	Håndtak OHYS3AH
4337037	1SCA022783R0170	HÅNDTAK OTV400ECK, I-0-II
4337805	1SCA022380R8930	HÅNDTAK RØD OHY 45J6
4337809	1SCA022381R0410	HÅNDTAK RØD OHY 80J6
4337804	1SCA022380R8770	HÅNDTAK SORT OHB 45J6
4337806	1SCA022380R9660	HÅNDTAK SORT OHB 65J6
4337814	1SCA022381R1560	HÅNDTAK SORT OHB125J12
4337888	1SCA022589R3340	HÅNDTAK SORT OHB125J12E011
4337848	1SCA022383R2480	HÅNDTAK SORT OHB65J6E011
4337839	1SCA022381R0830	HÅNDTAK SORT OHB95J12
4337849	1SCA022621R0760	HÅNDTAK SORT OHB95J12E011
4363500	1SCA109089R1001	HÅNDTAK SORT OHBS2
4337036	1SCA022783R0090	HÅNDTAK SORT OTV250ECK
4337038	1SCA022797R2470	HÅNDTAK SORT OTV800ECK
4337357	1SCA022301R5350	HÅNDTAK SORT YAST1

ABB AS, Low Voltage Products

Inngår i Part of
ABB AS

Adresse Address
Postboks 100 Sentrum
Amm. Aallsgt. 97
3701 SKIEN
Norway

Telefon Phone
Nasjonal 03500
International +47 22872000

Web:
www.abb.no/automasjonsprodukter
Product catalogue online:
www.abblvp.no

Foretaksregisteret
Register of Business Enterprises
NO982 085 160MVA



4337045
4337353
4337044
4337446
4337842
4337841
4337358
4337359

1SCA022098R9420
1SCA022071R2890
1SCA022071R3270
1SCA022467R5060
1SCA022456R9620
1SCA022456R9540
1SCA022763R2700
1SCA022763R2960

HÅNDTAK YASDA 21 I-O-II IP44
HÅNDTAK YASDA 6 I-O-II IP44
HÅNDTAK YASDA 8 I-O IP65
HÅNDTAKSTØTTE SORT OHZX5
OHG65J6T
OHY65J6T
OTV250EK HÅNDTAK PÅ BRYTER
OTV400EK HÅNDTAK PÅ BRYTER



ABB AS, Low Voltage Products

Inngår i Part of
ABB AS

Adresse Address
Postboks 100 Sentrum
Amm. Aallsgt. 97
3701 SKIEN
Norway

Telefon Phone
Nasjonal 03500
International +47 22872000

Web:
www.abb.no/automasjonsprodukter
Product catalogue online:
www.abblvp.no

Foretaksregisteret
Register of Business Enterprises
NO982 085 160MVA



Handled by
Matti Tuononen

Date
27/06/2014

Pages
1 (2)

Letter of confirmation

To whom it may concern

We hereby confirm that the listed ABB products can be used in ambients specified below:

OT16F...160E_ , OT16...125F_C_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.
 - o At - 40C the maximum number of cold starts is 100 operations.
 - o In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

OT200...4000E_ , OT160...3200E_C_ , OS32G_ ... OS1250_ , OTDC16_ ... 500_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.

ABB Oy

Low Voltage Products
Business Identity Code: 0763403-0 VAT-
code FI07634030
Domicile: Helsinki

Visiting Address
Muottitie 2 A
FI-65320 Vaasa
FINLAND

Postal Address
P.O. Box 622
FI-65101 Vaasa
FINLAND

Company Address
Strömbergintie 1
FI-00380 Helsinki
FINLAND

Telephone
+358 10 22 11
Telefax
+358 10 22 45708

Internet
www.abb.fi
e-mail:
first name.last name
@fi.abb.com

- At - 35C the endurance values according to the requirements of category B.
- In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

Yours faithfully



Martti Tuononen

Product manager