

FDV

8

ELnumber	Material No.	Material Discription
4337062	1SCA022771R7520	LASTBR.VENDER I-0-II OT200E3CP
4337001	1SCA022771R7280	LASTBR.VENDERI-0-II OT200E04CP
4337002	1SCA022771R3450	LASTBR.VENDERI-0-II OT250E03CP
4337075	1SCA022775R4640	LASTBR.VENDERI-0-II OT250E04CP
4337003	1SCA022772R6780	LASTBR.VENDERI-0-II OT315E03CP
4337004	1SCA022775R7150	LASTBR.VENDERI-0-II OT315E04CP
4337076	1SCA022771R8680	LASTBR.VENDERI-0-II OT315E04CP
4337074	1SCA022771R8500	LASTBR.VENDERI-0-II OT400E03CP
4337005	1SCA022785R6050	LASTBR.VENDERI-0-II OT630E03CP
4337006	1SCA022785R6130	LASTBR.VENDERI-0-II OT630E04CP



ABB AS, Low Voltage Products

Inngår i Part of
ABB AS

Adresse Address
Postboks 100 Sentrum
Amm. Aallsgt. 97
3701 SKIEN
Norway

Telefon Phone
Nasjonal 03500
International +47 22872000

Web:
www.abb.no/automasjonsprodukter
Product catalogue online:
www.abblvp.no

Foretaksregisteret
Register of Business Enterprises
NO982 085 160MVA



Handled by
Matti Tuononen

Date
27/06/2014

Pages
1 (2)

Letter of confirmation

To whom it may concern

We hereby confirm that the listed ABB products can be used in ambients specified below:

OT16F...160E_ , OT16...125F_C_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.
 - o At - 40C the maximum number of cold starts is 100 operations.
 - o In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

OT200...4000E_ , OT160...3200E_C_ , OS32G_ ... OS1250_ , OTDC16_ ... 500_

- Storage & transportation ambient temperatures
 - o - 40C ...+ 55C, short time (2h/24h) + 70C. Ambient humidity as specified in IEC60947-1 standard.
- Operation ambient temperatures
 - o Continuously - 5C ... + 35C, short time (2h/24h) + 40C, as specified in IEC60947-1 standard. Product ratings as shown in the documentation.

ABB Oy

Low Voltage Products
Business Identity Code: 0763403-0 VAT-Muotitie 2 A
code FI07634030
Domicile: Helsinki

Visiting Address
Muotitie 2 A
FI-65320 Vaasa
FINLAND

Postal Address
P.O. Box 622
FI-65101 Vaasa
FINLAND


Company Address
Strömbergintie 1
FI-00380 Helsinki
FINLAND

Telephone
+358 10 22 11
Telefax
+358 10 22 45708

Internet
www.abb.fi
e-mail:
first name.last name
@fi.abb.com

- At - 35C the endurance values according to the requirements of category B.
- In ambient temperatures over + 35C the current ratings must be derated according to the manufacturers instructions. Ambient humidity shall not exceed the level specified in the standard IEC60947-1.

Yours faithfully



Martti Tuononen

Product manager