

FDV dokumentasjon

Strømtrafo CT6	Typebetegnelse	Varenummer	EAN	El.nummer
	STRØMTRAFO CT6/250	2CSG421130R1101	8012542605508	8261031
	STRØMTRAFO CT6/300	2CSG421140R1101	8012542605607	8261032
	STRØMTRAFO CT6/400	2CSG421150R1101	8012542605706	8261033
	STRØMTRAFO CT6/500	2CSG421160R1101	8012542605805	8261034
	STRØMTRAFO CT6/600	2CSG421170R1101	8012542605904	8261035
	STRØMTRAFO CT6/800	2CSG421180R1101	8012542606000	8261036
	STRØMTRAFO CT6/1000	2CSG421190R1101	8012542606109	8261037
	STRØMTRAFO CT6/1200	2CSG421200R1101	8012542606208	8261038
	STRØMTRAFO CT6/1500	2CSG421220R1101	8012542606307	8261039
	STRØMTRAFO CT6/2000	2CSG421230R1101	8012542606406	8261040
	STRØMTRAFO CT6/2500	2CSG421240R1101	8012542606505	8261041

FDV	Strømtrafoer er produsert og testet i henhold til IEC EN 60044-1, IEC EN 61010-1		Ingen krav til periodisk vedlikehold.																																																																																																									
Tekniske Data																																																																																																												
	<table><tr><th colspan="5">Technical features</th></tr><tr><th></th><th></th><th>CT...</th><th>CTO</th><th>TRFM</th></tr><tr><td>Standard secondary current</td><td>[A]</td><td colspan="3">5A</td></tr><tr><td>Max. voltage for operation</td><td>[kV]</td><td colspan="3">1,2</td></tr><tr><td>Test voltage</td><td>[kV]</td><td colspan="3">3 a 50 Hz/1min</td></tr><tr><td>Residual current voltage at secondary terminals when security circuit intervenes (only SELV versions)</td><td></td><td colspan="3">< 25V rms</td></tr><tr><td>Short circuit rated thermal current</td><td>[IpN]</td><td>40 per 1 sec.</td><td>60 per 1 sec.</td><td>40 per 1 sec.</td></tr><tr><td>Short circuit rated dynamic current</td><td>[Ith]</td><td colspan="3">2,5 per 1 sec.</td></tr><tr><td>Permanent overload</td><td>[IpN]</td><td colspan="3">1,2</td></tr><tr><td>Safety factor</td><td>[Fs]</td><td colspan="3">< 5</td></tr><tr><td>Frequency</td><td>[Hz]</td><td colspan="3">50-60</td></tr><tr><td>Air insulation E class</td><td></td><td>Calss E</td><td>B</td><td>E</td></tr><tr><td>Terminals</td><td></td><td colspan="3">primary P1 - P2 (K - L); secondary s1 - s2 (k - l) P1 (K) primary winding input s1 (k) secondary winding input P2 (L) primary winding output s2 (l) secondary winding output</td></tr><tr><td>Housing</td><td></td><td>Latamid 66 H2 G25 V0</td><td colspan="2">Materiale termoplastico autoestinguente V0</td></tr><tr><td>Protection degree</td><td></td><td>IP30</td><td>IP20</td><td>IP20</td></tr><tr><td>Operating temperature</td><td>[°C]</td><td>-5...+50</td><td>-5...+50</td><td>-25...+50</td></tr><tr><td>Max. temperature on bars</td><td>[°C]</td><td colspan="3">70°C</td></tr><tr><td>Storage temperature</td><td>[°C]</td><td>-20...+90</td><td>-20...+80</td><td>-40...+80</td></tr><tr><td>Relative humidity</td><td></td><td colspan="3">80%</td></tr><tr><td>Reference standard</td><td></td><td colspan="3">IEC EN 60044-1, IEC EN 61010-1</td></tr><tr><td>Secondary protection circuit reference standards (only SELV versions)</td><td></td><td colspan="3">IEC60364; IEC473.1.4; IEC556.3; CEI64-8-4; CEI411.1.4.3; CEI411.5.2; CEI411.2; CEI473.1.4; CEI473.2.3</td></tr></table>				Technical features							CT...	CTO	TRFM	Standard secondary current	[A]	5A			Max. voltage for operation	[kV]	1,2			Test voltage	[kV]	3 a 50 Hz/1min			Residual current voltage at secondary terminals when security circuit intervenes (only SELV versions)		< 25V rms			Short circuit rated thermal current	[IpN]	40 per 1 sec.	60 per 1 sec.	40 per 1 sec.	Short circuit rated dynamic current	[Ith]	2,5 per 1 sec.			Permanent overload	[IpN]	1,2			Safety factor	[Fs]	< 5			Frequency	[Hz]	50-60			Air insulation E class		Calss E	B	E	Terminals		primary P1 - P2 (K - L); secondary s1 - s2 (k - l) P1 (K) primary winding input s1 (k) secondary winding input P2 (L) primary winding output s2 (l) secondary winding output			Housing		Latamid 66 H2 G25 V0	Materiale termoplastico autoestinguente V0		Protection degree		IP30	IP20	IP20	Operating temperature	[°C]	-5...+50	-5...+50	-25...+50	Max. temperature on bars	[°C]	70°C			Storage temperature	[°C]	-20...+90	-20...+80	-40...+80	Relative humidity		80%			Reference standard		IEC EN 60044-1, IEC EN 61010-1			Secondary protection circuit reference standards (only SELV versions)		IEC60364; IEC473.1.4; IEC556.3; CEI64-8-4; CEI411.1.4.3; CEI411.5.2; CEI411.2; CEI473.1.4; CEI473.2.3	
Technical features																																																																																																												
		CT...	CTO	TRFM																																																																																																								
Standard secondary current	[A]	5A																																																																																																										
Max. voltage for operation	[kV]	1,2																																																																																																										
Test voltage	[kV]	3 a 50 Hz/1min																																																																																																										
Residual current voltage at secondary terminals when security circuit intervenes (only SELV versions)		< 25V rms																																																																																																										
Short circuit rated thermal current	[IpN]	40 per 1 sec.	60 per 1 sec.	40 per 1 sec.																																																																																																								
Short circuit rated dynamic current	[Ith]	2,5 per 1 sec.																																																																																																										
Permanent overload	[IpN]	1,2																																																																																																										
Safety factor	[Fs]	< 5																																																																																																										
Frequency	[Hz]	50-60																																																																																																										
Air insulation E class		Calss E	B	E																																																																																																								
Terminals		primary P1 - P2 (K - L); secondary s1 - s2 (k - l) P1 (K) primary winding input s1 (k) secondary winding input P2 (L) primary winding output s2 (l) secondary winding output																																																																																																										
Housing		Latamid 66 H2 G25 V0	Materiale termoplastico autoestinguente V0																																																																																																									
Protection degree		IP30	IP20	IP20																																																																																																								
Operating temperature	[°C]	-5...+50	-5...+50	-25...+50																																																																																																								
Max. temperature on bars	[°C]	70°C																																																																																																										
Storage temperature	[°C]	-20...+90	-20...+80	-40...+80																																																																																																								
Relative humidity		80%																																																																																																										
Reference standard		IEC EN 60044-1, IEC EN 61010-1																																																																																																										
Secondary protection circuit reference standards (only SELV versions)		IEC60364; IEC473.1.4; IEC556.3; CEI64-8-4; CEI411.1.4.3; CEI411.5.2; CEI411.2; CEI473.1.4; CEI473.2.3																																																																																																										
	CT6 Front view dimensions: 121 (height), 100 (width), 105 (base width), 75 (top width), 18.5 (top thickness), 61 (bottom width). Side view dimensions: 21 (top flange). Top view dimensions: 62 (width), 64.7 (depth). Central section dimensions: 51.3 (height), 30.4 (width), 54.4 (base width), 3.7 (top thickness). Central section																																																																																																											
Produsent	Navn	Adresse	Tlf.	E-post																																																																																																								
	ABB AS	Bergerveien 12 1396 Billingstad	03500	automasjonsprodukter@no.abb.com																																																																																																								