

FDV dokumentasjon

Arbeids- strømsut- løser	Typebetegnelse	Varenummer	EAN	El.nummer
F2C-Ax	Arb.strømutl.F2C-A1 AC/DC12-60	2CSS200933R0011	8012542974901	1665791
	Arb.strømutl.F2C-A2 AC110-415V	2CSS200933R0012	8012542975007	1665792

FDV						Ingen krav til periodisk vedlikehold.																																																																																																																																																																																											
Tekniske Data	Shunt trip for F 200 RCCBs <table border="1"> <thead> <tr> <th colspan="3"></th> <th colspan="5">F2C-A1</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Rated voltage</td> <td>AC</td> <td>V</td> <td colspan="5">12...60</td> </tr> <tr> <td>DC</td> <td>V</td> <td colspan="5">12...60</td> </tr> <tr> <td>Max release duration</td> <td></td> <td>ms</td> <td colspan="5">10</td> </tr> <tr> <td rowspan="2">Min. release voltage</td> <td>AC</td> <td>V</td> <td colspan="5">6</td> </tr> <tr> <td>DC</td> <td>V</td> <td colspan="5">4.5</td> </tr> <tr> <td rowspan="2">Consumption on release</td> <td>Ub</td> <td>V</td> <td>12 DC</td> <td>12 AC</td> <td>24 DC</td> <td>60 DC</td> <td>60 AC</td> </tr> <tr> <td>Ib max</td> <td>A</td> <td>0.88</td> <td>0.65</td> <td>1.58</td> <td>5.8</td> <td>5</td> </tr> <tr> <td>Coil resistance</td> <td></td> <td>Ω</td> <td colspan="5">5.5</td> </tr> <tr> <td>Terminals</td> <td></td> <td>mm²</td> <td colspan="5">2x1.5</td> </tr> <tr> <td>Tightening torque</td> <td></td> <td>Nm</td> <td colspan="5">0.2</td> </tr> <tr> <td>Dimensions (H x D x W)</td> <td></td> <td>mm</td> <td colspan="5">85 x 69 x 17.5</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="3"></th> <th colspan="5">F2C-A2</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Rated voltage</td> <td>AC</td> <td>V</td> <td colspan="5">110...415</td> </tr> <tr> <td>DC</td> <td>V</td> <td colspan="5">110...250</td> </tr> <tr> <td>Max release duration</td> <td></td> <td>ms</td> <td colspan="5">10</td> </tr> <tr> <td rowspan="2">Min. release voltage</td> <td>AC</td> <td>V</td> <td colspan="5">75</td> </tr> <tr> <td>DC</td> <td>V</td> <td colspan="5">55</td> </tr> <tr> <td rowspan="2">Consumption on release</td> <td>Ub</td> <td>V</td> <td>110 DC</td> <td>110 AC</td> <td>250 DC</td> <td>415 AC</td> <td></td> </tr> <tr> <td>Ib max</td> <td>A</td> <td>0.05</td> <td>0.03</td> <td>0.1</td> <td>0.16</td> <td></td> </tr> <tr> <td>Coil resistance</td> <td></td> <td>Ω</td> <td colspan="5">1355</td> </tr> <tr> <td>Terminals</td> <td></td> <td>mm²</td> <td colspan="5">2x1.5</td> </tr> <tr> <td>Tightening torque</td> <td></td> <td>Nm</td> <td colspan="5">0.2</td> </tr> <tr> <td>Dimensions (H x D x W)</td> <td></td> <td>mm</td> <td colspan="5">85 x 69 x 17.5</td> </tr> </tbody> </table>										F2C-A1					Rated voltage	AC	V	12...60					DC	V	12...60					Max release duration		ms	10					Min. release voltage	AC	V	6					DC	V	4.5					Consumption on release	Ub	V	12 DC	12 AC	24 DC	60 DC	60 AC	Ib max	A	0.88	0.65	1.58	5.8	5	Coil resistance		Ω	5.5					Terminals		mm ²	2x1.5					Tightening torque		Nm	0.2					Dimensions (H x D x W)		mm	85 x 69 x 17.5								F2C-A2					Rated voltage	AC	V	110...415					DC	V	110...250					Max release duration		ms	10					Min. release voltage	AC	V	75					DC	V	55					Consumption on release	Ub	V	110 DC	110 AC	250 DC	415 AC		Ib max	A	0.05	0.03	0.1	0.16		Coil resistance		Ω	1355					Terminals		mm ²	2x1.5					Tightening torque		Nm	0.2					Dimensions (H x D x W)		mm	85 x 69 x 17.5				
				F2C-A1																																																																																																																																																																																													
Rated voltage	AC	V	12...60																																																																																																																																																																																														
	DC	V	12...60																																																																																																																																																																																														
Max release duration		ms	10																																																																																																																																																																																														
Min. release voltage	AC	V	6																																																																																																																																																																																														
	DC	V	4.5																																																																																																																																																																																														
Consumption on release	Ub	V	12 DC	12 AC	24 DC	60 DC	60 AC																																																																																																																																																																																										
	Ib max	A	0.88	0.65	1.58	5.8	5																																																																																																																																																																																										
Coil resistance		Ω	5.5																																																																																																																																																																																														
Terminals		mm ²	2x1.5																																																																																																																																																																																														
Tightening torque		Nm	0.2																																																																																																																																																																																														
Dimensions (H x D x W)		mm	85 x 69 x 17.5																																																																																																																																																																																														
			F2C-A2																																																																																																																																																																																														
Rated voltage	AC	V	110...415																																																																																																																																																																																														
	DC	V	110...250																																																																																																																																																																																														
Max release duration		ms	10																																																																																																																																																																																														
Min. release voltage	AC	V	75																																																																																																																																																																																														
	DC	V	55																																																																																																																																																																																														
Consumption on release	Ub	V	110 DC	110 AC	250 DC	415 AC																																																																																																																																																																																											
	Ib max	A	0.05	0.03	0.1	0.16																																																																																																																																																																																											
Coil resistance		Ω	1355																																																																																																																																																																																														
Terminals		mm ²	2x1.5																																																																																																																																																																																														
Tightening torque		Nm	0.2																																																																																																																																																																																														
Dimensions (H x D x W)		mm	85 x 69 x 17.5																																																																																																																																																																																														
	S 2C-UA... F 2C-A... S 2C-OVP The drawing shows two views of the device. The left view is a side profile showing a height of 85 mm and a width of 17.4 mm. The right view is a front view showing a width of 74 mm and a height of 45 mm. A dimension of 6.8 mm is indicated for the mounting flange.																																																																																																																																																																																																
Produsent	Navn	Adresse	Tlf.		E-post																																																																																																																																																																																												
	ABB AS	Bergerveien 12 1396 Billingstad	03500		automasjonsprodukter@no.abb.com																																																																																																																																																																																												