

FDV dokumentasjon

Automa- tiske gjeninn- kobler F2C-ARH	Typebetegnelse	Varenummer	EAN	El.nummer
	Auto.gjen.innkobl.F2C-ARH	2CSF200992R0005	8012542732433	1630530

FDV						Ingen krav til periodisk vedlikehold.																																	
Tekniske Data	Home automatic resetting unit <table border="1"> <thead> <tr> <th></th> <th></th> <th>F2C-ARH /F2C-ARH-T</th> </tr> </thead> <tbody> <tr> <td>Power supply</td> <td>VAC</td> <td>230</td> </tr> <tr> <td>Number of automatic reclosing attempts</td> <td></td> <td>1</td> </tr> <tr> <td>Reset time for counter of automatic reclosing attempts</td> <td>sec</td> <td>12</td> </tr> <tr> <td>Power absorbed during the operation</td> <td>VA</td> <td>(t<0.5s) 20 max</td> </tr> <tr> <td>Power consumption in stand-by</td> <td>W</td> <td>0.4 max</td> </tr> <tr> <td>Number of operations</td> <td></td> <td>≤ 10,000</td> </tr> <tr> <td>Operating temperature</td> <td>°C</td> <td>-25 ... + 55</td> </tr> <tr> <td>Signal contact cable section</td> <td>mm²</td> <td>≤ 2.5</td> </tr> <tr> <td>Signal contact for the locked state (terminals 1-2)</td> <td></td> <td>1NA (change-over contact)</td> </tr> <tr> <td>Signal contact rated current</td> <td>A</td> <td>3 (250V AC)</td> </tr> </tbody> </table>								F2C-ARH /F2C-ARH-T	Power supply	VAC	230	Number of automatic reclosing attempts		1	Reset time for counter of automatic reclosing attempts	sec	12	Power absorbed during the operation	VA	(t<0.5s) 20 max	Power consumption in stand-by	W	0.4 max	Number of operations		≤ 10,000	Operating temperature	°C	-25 ... + 55	Signal contact cable section	mm²	≤ 2.5	Signal contact for the locked state (terminals 1-2)		1NA (change-over contact)	Signal contact rated current	A	3 (250V AC)
			F2C-ARH /F2C-ARH-T																																				
Power supply	VAC	230																																					
Number of automatic reclosing attempts		1																																					
Reset time for counter of automatic reclosing attempts	sec	12																																					
Power absorbed during the operation	VA	(t<0.5s) 20 max																																					
Power consumption in stand-by	W	0.4 max																																					
Number of operations		≤ 10,000																																					
Operating temperature	°C	-25 ... + 55																																					
Signal contact cable section	mm²	≤ 2.5																																					
Signal contact for the locked state (terminals 1-2)		1NA (change-over contact)																																					
Signal contact rated current	A	3 (250V AC)																																					
Produsent	Navn	Adresse	Tlf.		E-post																																		
	ABB AS	Bergerveien 12 1396 Billingstad	03500		automasjonsprodukter@no.abb.com																																		