

FDV dokumentasjon

Samle-skinne	Typebetegnelse	Varenummer	EAN	El.nummer
S800-BB250	Skinne 3fase S800-BB250 Mateblokk S803-BBPC120 Isolator til BB250 S800-BBIC Endedeksel til BB250 S800-END	2CCS800900R0071 2CCS800900R0101 2CCS800900R0081 2CCS800900R0091	7612271208288 7612271208301 7612271208967 7612271208295	1628880 1628881 1628882 1628883

FDV	Ingen krav til periodisk vedlikehold.
-----	---------------------------------------

Tekniske
Data

Busbar S803-BB250

Max. rated continuous current in	Side supply	[A]	125
	Central supply	[A]	250
Conditional short circuit current I _p		[kA eff]	100 protected by Tmax
Poles			3
Rated operating voltage U _e (AC)		[V]	400/690
50/60Hz			
Rated insulation voltage U _i		[V]	690
Rated impulse withstand voltage U _{imp}		[kV]	8
Rated frequency		[Hz]	50
Standards			EN 60439-2:2000
Material of the bars			E-Cu 58 half-hard rolled F25
Material of the insulation profile			Cycloley C 3500; UL94 V-0 at 1.5mm
Material of the end caps			Polyamide PA66+PA6; UL94 V-0 at 0.4mm Free of halogen and phosphorus
Busbar cross-sections		[mm²]	60
Overvoltage category			III
Pollution degree			2

Busbar Power Connector S803-BBPC120

Max. rated continuous current in	[A]	250
Poles		3
Rated operating voltage U _e	[V]	400/690
Rated frequency	[Hz]	50
Standards		EN 60439-2:2000
Material of the terminals		CuZn39Pb2; material no.: 2.0380
Casing material		Polyamide PA66+PA6; UL94 V-0 at 0.4mm Free of halogen and phosphorus
Tightening torque		
At supply end	[Nm]	19
At busbar end	[Nm]	3
Connection cross-section	[mm²]	1.6...120
Pollution degree		2

Technical drawings of the busbar system. The main drawing shows a 3-phase busbar assembly with dimensions: total width 651, height 141, and terminal spacing 27. A detail shows a terminal with dimensions 8, 3, 73.25, and 27. Another detail shows a terminal with dimensions 79, 27, and 73.25. A side view shows a terminal with dimensions 56.25 and 30.

Produsent	Navn	Adresse	Tlf.	E-post
	ABB AS	Bergerveien 12 1396 Billingstad	03500	automasjonsprodukter@no.abb.com