



Wireless Shading control 55mm, preconfigured

Part no. CPAD-00/214
 Article no. Y7-193729
 Catalog No. 193729

Delivery program

Product Type		Packaged Units Actuator Pushbutton
Mounting type		Flush mounted Surface mounted
Power supply		Battery Mains
Actuation Function		Shading
Pushbutton compatibility		55 mm (Universal)
Rocker Pitch		1-gang
Color		Pure White

Technical data ETIM 6.0

Installation bus systems (EG000032) / Shutting actuator for bus system (EC001330)		
Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Shutting actuator for bus system (ecl@ss8.1-27-14-31-28 [AKE296011])		
Bus system KNX		No
Bus system KNX radio		No
Bus system radio frequent		Yes
Bus system LON		No
Bus system Powernet		No
Other bus systems		Other
Radio frequent bidirectional		Yes
Mounting method		Flush mounted (plaster)
Width in number of modular spacings		3
Bus connection included		Yes
Bus module detachable		No
Local operation/hand operation		No
With LED indication		Yes
Number of inputs		0
Switching current (resistive)	A	6
Max. switching power	W	1380
Max. number of venetian-blind outputs		1
With switch function		Yes
Type of current		AC
Degree of protection (IP)		IP20

Additional product information (links)

(IL019194ZU)CPAD	
(IL019194ZU)CPAD	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211192_2018_01.pdf