



Auxiliary contact, for PLS, postal Code, PKNM, ZP-A40, ZP-ASA, Z-MS, 2W, 0.5HP

Part no. ZP-NHK
Article no. 248437

Delivery program

Basic function			Accessories for combined residual-current/power circuit-breakers Accessories for miniature circuit breaker
Basic function accessories			Tripping signal contacts
Application			Switchgear for industrial and advanced commercial applications
Product range			Accessory
Side mounting			for fitting on left to: LS, FI/LS
Contact sequence			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	°C	-5	
Operating ambient temperature max.	°C	40	

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Auxiliary contact unit for distribution board (EC001286)			
Electric engineering, automation, process control engineering / Electrical installation, device / Breaker switch component / Auxiliary contact unit for distribution board (ecl@ss8.1-27-14-35-02 [AKE327010])			
Device fitting			Universal
Additional equipment			Signalling switch
Attached at delivery			No
Assembly width (TE)			0.5
Number of normally open contacts			0
Number of normally closed contacts			0
Number of change-over contacts			2
Number of fault-signal switches			0
Rated switch current	A	4	
Nominal rated voltage	V	250	
Control voltage type			AC
With autotest for earth leakage function			No
Suitable for max. number of poles main contact unit (total)			2
Suitable for max. current main contact unit	A	4	

Dimensions

