



Wireless Dimming 55mm, preconfigured

Part no. **CPAD-00/213**
 Article no. **Y7-193728**
 Catalog No. **193728**

Delivery program

Product Type		Packaged Units Actuator Pushbutton
Mounting type		Flush mounted Surface mounted
Power supply		Battery Mains
Actuation Function		Dimming
Pushbutton compatibility		55 mm (Universal)
Rocker Pitch		1-gang
Color		Pure White

Technical data ETIM 6.0

Installation bus systems (EG000032) / Dimming actuator for bus system (EC001094)		
Electric engineering, automation, process control engineering / Electrical installation, device / Bus system / Bus system dimming actuator (ecl@ss8.1-27-14-31-23 [AKE291012])		
Bus system KNX		No
Bus system KNX radio		No
Bus system radio frequent		Yes
Bus system LON		No
Bus system Powernet		No
Other bus systems		Other
Radio frequent bidirectional		Yes
Model		Dimming actuator
Mounting method		Flush mounted (plaster)
Width in number of modular spacings		3
Bus connection included		Yes
Bus module detachable		No
Substation input		No
Local operation/hand operation		No
With LED indication		Yes
Number of outputs		1
Output power	W	0 - 250
Power boost suitable		No
Type of load		Universal and LED Retrofit
Max. control current	mA	0
Voltage	V	196 - 253
Parallel-service possible		No
Frequency	Hz	50 - 50
Degree of protection (IP)		IP20

Additional product information (links)

(IL019193ZU)CPAD	
(IL019193ZU)CPAD	ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/MA136211191_2018_01.pdf