

According to IEC 60947-3, EN 60947-3, VDE 0660 part 107



Rated Thermal Current $I_U/I_{th}/I_{the}$					
				A	80
Rated Insulation Voltage U_i ¹					
				V	690
Rated Impulse Withstand Voltage U_{imp}					
				kV	6
Rated Operational Current I_e					
AC-21A	Switching of resistive loads, including moderate overloads			A	80
AC-22A	Switching of combined resistive or low inductive loads including moderate overloads		220 V–500 V 660 V–690 V	A	80 65
Rated Utilization Category					
AC-3	Direct-on-line starting	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	15 22 30 18,5
AC-23A	Frequent switching of motors or other high inductive loads	3 phase, 3 pole	220 V–240 V 380 V–440 V 500 V 660 V–690 V	kW	18,5 30 37 22
Short Circuit Protection					
Max. fuse size		gG-characteristic		A	80
Rated short-time withstand current		(1 s-current)		A	1600
For connections with insulated ring and fork type cable terminal - copper wires only					
Single-core or stranded wire				mm ²	50
Flexible wire				mm ²	35
Flexible wire with sleeving in accordance with DIN 46228				mm ²	35

¹ Valid for lines with grounded common neutral termination, overvoltage category III, Other values on request.

Miscellaneous

Minimum Voltage:	on request	
Power loss per contact at I_U :	1,7 W	
Resistance to vibration:	min. 4 g, 2-100 Hz, 1,6 mm	
Resistance to shock:	min. 6 g, 6 ms	
Ambient Temperature of Stages :	open at 100 % I_U/I_{th} enclosed at 100 % I_{the}	50 °C during 24 hours with peaks up to 55 °C 35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5 °C no shock load permissible)	

Approvals and Standards

IEC 60947 EN 60947						
-----------------------	---	---	--	---	---	---

* for KG80 only

USA / Canada



Rated Thermal Current $I_U/I_{th}/I_{the}$					
				A	80
Rated Insulation Voltage U_i					
				V	600
Rated Operational Current I_e					
Pilot Duty:			Heavy	VAC	A600
Ampere Rating	Resistive or low inductive loads	ON/OFF 1-0-2	600 V 600 V	A	80 80
Max. Permissible Wire Gage - copper wires only					
	Single-core or stranded wire			AWG	1/0
	Flexible wire: AWG wire (without sleeving)			AWG	2
Ratings					
	Standard motor load, DOL-Rating (similar AC-3)	3 phase 3 pole	110 V – 120 V 220 V – 240 V 440 V – 480 V 550 V – 600 V	HP	7,5 20 40 50

Miscellaneous

Minimum Voltage:	on request	
Power loss per contact at I_U:	1,7 W	
Resistance to vibration:	min. 4 g, 2-100 Hz, 1,6 mm	
Resistance to shock:	min. 6 g, 6 ms	
Ambient Temperature of Stages :	open at 100 % I_U/I_{th} enclosed at 100 % I_{the}	50 °C during 24 hours with peaks up to 55 °C 35 °C during 24 hours with peaks up to 40 °C
Storage temperature:	-40 °C to 85 °C (in case of temperature below -5 °C no shock load permissible)	

Approvals and Standards

IEC 60947 EN 60947			 GB14048.3	 *	 CH01	
-----------------------	---	---	---	---	---	---

* for KG80 only