

POWER SUPPLY FOR CONSTANT LOAD PRIM 85..265V AC,
85..300V DC SEC 24V DC +- 5% MOUNTING WIDTH 2WU (WIDTH
UNIT) SHORT CIRCUIT AND OVERLOAD PROTECTION



Model	
Product brand name	SENTRON
Product designation	Power supply unit
Design of the transformer	Power transformer
General technical data	
Supplied active power / maximum	8.4 W
Voltage	
Input voltage	265 V
Output voltage	
• _1 / rated value	24 V
• _2 / rated value	0 V
• _3 / rated value	0 V
Dissipation	
Power loss [W]	
• maximum	0 W
Electricity	
Output current	

• maximum	0.35 A
• _1 / rated value	0.35 A
• _2 / rated value	0 A
• _3 / rated value	0 A

Suitability

Suitability for integration

• surface-mounted installation	No
• flush mounting	No

Product details

Product component / switch	No
----------------------------	----

Product function

Product function / Thermal protection	Yes
---------------------------------------	-----

Inputs Outputs

Property of the output / Short-circuit proof	Yes
--	-----

Mechanical Design

Height	64 mm
Width	36 mm
Length	90 mm
Number of width units	2
Mounting type / Side-by-side mounting	Yes

General Product Approval	other
--------------------------	-------

[Confirmation](#)



Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4AC2402>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/4AC2402>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=4AC2402

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



