



NEOZED FUSE LINK 400V GL, SIZE D01,
6A IN FOLDING BOX

Similar to image

Technical data:		
Color coding of the fuse link		green
Current / for AC / rated value	A	6
Size of the fallback-system / acc. to DIN EN 60269-1		D01
Supply voltage		
• for AC / rated value	V	400
Switching capacity current / in accordance with IEC 60947-2 / rated value	kA	50
Ambient temperature		
• minimum	°C	-5
• maximum	°C	40

Certificates/approvals:		
General Product Approval	Declaration of Conformity	Test Certificates
 GOST	 VDE	 ÖVE
 EG-Konf.	Special Test Certificate	Type Test Certificates/Test Report
other		
Environmental Confirmations		

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5SE2306/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2306

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

Datanorm [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)



last change:

Nov 4, 2012