



## JUNCTION BOX

# WK 040-L



## WK 040-L

### Junction box

87 x 87 x 45 mm

Article number: 40490701

Junction box acc. DIN EN 60670 (VDE 0606),  $U_i=690V$ , Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M20, seal range 8 - 13.5 mm

grey, without terminal



## Technical data

### Measures

|         |       |
|---------|-------|
| Width:  | 87 mm |
| Length: | 87 mm |
| Height: | 45 mm |

### Material

|              |                         |
|--------------|-------------------------|
| Base:        | Duroplastic             |
| Cover:       | Duroplastic             |
| Sealing:     | thermoplastic elastomer |
| Cover screw: | Steel                   |

### Other attributes

|                              |                   |
|------------------------------|-------------------|
| Entries:                     | 6                 |
| Rated cross section:         | 4 mm <sup>2</sup> |
| Tackable:                    | No                |
| Rated insulation voltage AC: | 690 V             |

## Accessory

KVR M20-GDB/MGM

VST M20-or

AST M20-or

DMS M20

AST M20

KVR M20-GDB

KVR M20

GMU PA M20

ADR M20

WST M20

WNI M20

VST M20

VSS PA M20

SNI M20

BST M20

KS M20

DMS M20/sw



## JUNCTION BOX

# WK 040-L

|                     |                                       |
|---------------------|---------------------------------------|
| Explosion safety:   | none                                  |
| Fire protection:    | none                                  |
| sealable:           | No                                    |
| Heavy metals-free:  | Yes                                   |
| PVC-free:           | Yes                                   |
| Silicone-free:      | Yes                                   |
| Ingress protection: | IP54 - acc. EN 60529 / DIN VDE 0470-1 |
| Weatherproof:       | No                                    |
| Equipment:          | None                                  |
| Color:              | grey                                  |

## Environmental attributes

|                                            |        |
|--------------------------------------------|--------|
| Ambient temperature (min.):                | -25 °C |
| Ambient temperature (max.):                | 40 °C  |
| Ambient temperature (24 h):                | 35 °C  |
| Max. rel. humidity at 25° C (short Therm): | 95%    |
| Max. rel. humidity at 40° C:               | 50%    |

RST M20

Abox 025/040 KLS-2,5<sup>2</sup>/4<sup>2</sup>

WST M20/sw

WNI M20/sw

KVR M20-MGM/sw

KVR M20-GDB/MGM/sw

MPS-KRI

KVR M20-MGM

KVR M20-GDB/MGM

VST M20-or

AST M20-or

DMS M20

AST M20