



JUNCTION BOX

WK 100-L



WK 100-L

Junction box

115 x 115 x 66 mm

Article number: 41090601

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M32, seal range 13 - 23 mm, with sealing kit

grey, without terminal



Technical data

Measures

Width:	115 mm
Length:	115 mm
Height:	66 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	6
Rated cross section:	10 mm²
Tackable:	No
Rated insulation voltage AC:	690 V

Accessory

KVR M32-MGM

VST M32-or

AST M32-or

DMS M32

AST M32

WK 100 KLS-10²

KVR M32

GMU PA M32

ADR M32

WST M32

VST M32

VSS PA M32

SNI M32

KS M32

KST M32

WNI M32

RST M32



JUNCTION BOX

WK 100-L

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	None
Color:	grey

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

DMS M32/sw

KVR M32-MGM/sw

DMS M32/4

MPS-KRI

KVR M32-MGM

VST M32-or

AST M32-or

DMS M32

AST M32

WK 100 KLS-10²

KVR M32

GMU PA M32

ADR M32