



JUNCTION BOX

WK 007-2,5²



WK 007-2,5²

Junction box

80 x 80 x 38 mm

Article number: 40240701

Junction box acc. DIN EN 60670 (VDE 0606), Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M16, seal range 6 - 10 mm

grey, with screw terminal 5-poles - 2.5 mm², (6 x 1.5² / 4 x 2.5²)

IP54

2,5²

IK05



400V
AC



Technical data

Measures

Width:	80 mm
Length:	80 mm
Height:	38 mm

Material

Base:	Duroplastic
Cover:	Duroplastic
Sealing:	thermoplastic elastomer
Cover screw:	Steel

Other attributes

Entries:	7
Rated cross section:	2,5 mm ²
Tackable:	No
Rated insulation voltage AC:	400 V

Accessory

KVR M16-MGM

AST M16

KVR M16

GMU PA M16

ADR M16

WST M16

WNI M16

VST M16

VSS PA M16

RST M16

WK 007 KLS-2,5²

WST M16/sw

WNI M16/sw

DMS M16

MPS-KRI

KVR M16-MGM

AST M16



JUNCTION BOX

WK 007-2,5²

Explosion safety:	none
Fire protection:	none
sealable:	No
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP54 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	grey

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

KVR M16
GMU PA M16
ADR M16
WST M16
WNI M16
VST M16
VSS PA M16
RST M16
WK 007 KLS-2,5²
WST M16/sw
WNI M16/sw
DMS M16
MPS-KRI