



JUNCTION BOX

Abox 025-2,5²/w



Abox 025-2,5²/w

Junction box

CUSTOMIZABLE

80 x 80 x 52 mm
Article number: 80210701

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

white, with screw terminal, 5-poles - 2.5 mm² (4 x 1.5² / 4 x 2.5²)



Technical data

Measures

Width:	80 mm
Length:	80 mm
Height:	52 mm

Material

Base:	polystrole, membrane out of TPE
Cover:	Polystyrene

Other attributes

Entries:	8
Rated cross section:	2,5 mm²
Tackable:	No
Rated insulation voltage AC:	690 V
Fire protection:	none

Accessory

Abox 025/040 KLS-2,5²/4²

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M20-GDB/MGM

KVR M20-MGM

VST M20-or

AST M20-or

DMS M20

AST M20

KVR M20-GDB

KVR M20



JUNCTION BOX

Abox 025-2,5²/w

sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equiptment:	Terminal
Color:	white

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%

GMU PA M20
ADR M20
WST M20
WNI M20
VST M20
VSS PA M20
SNI M20
BST M20
KS M20
Abox PST
DMS M20/sw
RST M20
HandyQuick SQ51