



JUNCTION BOX

Abox 040-4,0²/w



Abox 040-4,0²/w

Junction box

CUSTOMIZABLE

93 x 93 x 55 mm
Article number: 80410701

Junction box acc. DIN EN 60670 (VDE 0606), Ui=690V, with self-sealing, soft inlet membranes, M20, seal range 2 - 16 mm

white, with screw terminal, 5-poles - 2.5/4.0 mm² (4 x 1.5² / 4 x 2.5² / 3 x 4.0²)



Technical data

Measures

Width:	93 mm
Length:	93 mm
Height:	55 mm

Material

Base:	polystrole, membrane out of TPE
Cover:	Polystyrene

Other attributes

Entries:	8
Rated cross section:	4 mm ²
Tackable:	No
Rated insulation voltage AC:	690 V
Explosion safety:	none

Accessory

HandyQuick SQ 52

HandyQuick SQ 32

HandyClip VC 21

HandyClip VC 20

HandyGrip VG 21 w

HandyGrip VG 20 w

HandyGrip VG 21

HandyGrip VG 20

KVR M20-GDB/MGM

AST M20

KVR M20-GDB

KVR M20

GMU PA M20

ADR M20

WST M20

WNI M20

VST M20



JUNCTION BOX

Abox 040-4,0²/w

Fire protection:	none
sealable:	Yes
Heavy metals-free:	Yes
PVC-free:	Yes
Silicone-free:	Yes
Ingress protection:	IP65 - acc. EN 60529 / DIN VDE 0470-1
Weatherproof:	No
Equipment:	Terminal
Color:	white

VSS PA M20
SNI M20
BST M20
KS M20
Abox PST
DMS M20/sw
RST M20
HandyQuick SQ51
HandyQuick SQ81
Abox 025/040 KLS-2,5 ² /4 ²
HandyQuick SQ 31
WST M20/sw
WNI M20/sw

Environmental attributes

Ambient temperature (min.):	-25 °C
Ambient temperature (max.):	40 °C
Ambient temperature (24 h):	35 °C
Max. rel. humidity at 25° C (short Therm):	95%
Max. rel. humidity at 40° C:	50%